

# Infoschedular by MMD

Available in either beautiful solid oak or a Eurostyle aluminum encased model, the Director is designed for high-visibility indoor use. Locations include lobbies, offices, conference rooms, showrooms, boardrooms, movie theater entrance ways or any area that requires an eye-catching message center.

At a glance, the Infoschedular clearly provides your visitors, guests or your customers with messages, schedules and the information they require. The not only keeps your customers informed, but most importantly, keeps your traffic flowing. The Infoschedular

You control the messaging via a hand-held remote or a PC. Update and revise your messages at any time. Easy-to-install and use, the Infoschedular is a complete turnkey solution. When instant timely information is required Message software has preview & message scheduling, (messages will automatically update through the week) Network from pc from wireless – hard wire to Ethernet



## High- Visibility, Indoor Message Center

Direct or inform clients, guests or employees. With characters displayed in three vivid colors, the Director is perfect for these applications:



Stores & displays pages of messages according to time and day of week  
Flexibility of 1- to 8-lines of messages  
7 Operating modes consisting of Hold, Wipe (four directions), Automode™ and Flash  
2 year ltd parts & labor warranty

Keyboard programmable from 30 ft.  
Standard packaging includes display, basic messaging software or optional scheduling software, 25 ft. cable, 9-pin adapter, IR remote, and installation instructions

# Infoschedular Specifications

Oak wall mounted	16 characters	Aluminum wall mounted	16 characters	24 characters
Length	22.50" (57.15cm)	Length	25.45" (64.64cm)	35.03" (88.97cm)
Height	27" (68.58cm)	Height	27.49" (69.82cm)	27.49" (69.82cm)
Depth	3.12" (7.93cm)	Depth	3.00" (7.62cm)	3.00" (7.62cm)
Weight	37lbs. (16.78kg.)	Weight	30lbs. (13.64kg.)	40lbs. (18.18kg.)

Oak with brochure rack/stand	16 characters	Aluminum with stand	16 characters	24 characters
Length	27" (68.58cm)	Length	25.45" (64.64cm)	35.03" (88.97cm)
Height	61" (154.94cm)	Height	68.04" (172.82cm)	68.04" (172.82cm)
Depth	*18" (45.72cm)	Depth	*20.00" (50.8cm)	*20.00" (50.8cm)
Weight	65lbs. (29.48kg.)	Weight	85lbs. (38.64kg.)	95lbs. (43.18kg.)

\*Reflects width of floor stand

<b>Oak Display Dimensions:</b>	16 characters—19"L x 16.8"H (48.26cm x 42.67cm)
<b>Aluminum Display Dimensions:</b>	16 characters—19"L x 16.8"H (48.26cm x 42.67cm) 24 characters—27.5"L x 16.8"H (69.85cm x 42.67cm)
<b>Oak Display Array:</b>	1.4", 16 characters x 8 lines
<b>Aluminum Display Array:</b>	1.4", 16 characters x 8 lines 1.4", 24 characters x 8 lines
<b>Pixel (LED) Color:</b>	Tricolor (red, green, and amber)
<b>Center-to-Center Pixel Spacing (Pitch):</b>	0.2" (0.51 cm)
<b>Character Column Pitch:</b>	0.4" (1.02cm) space between characters
<b>Character Row Pitch:</b>	1" (2.54cm) space between lines
<b>Character Size:</b>	1.4" tall x 1.0" wide (3.556 cm x 2.54 cm) (visible from 75 ft)
<b>Character Array:</b>	5" x 7" matrix (12.7cm x 17.78cm)
<b>Character Set:</b>	Sans serif upper/lower case Small sans serif
<b>Memory Retention:</b>	One month typical
<b>Message Capacity:</b>	26 different pages can be stored, scheduled, and displayed according to time and day of the week when using the IR remote control
<b>Message Operating Modes:</b>	7, Consisting of: Automode - Hold, Wipe (four directions), and Flash (character or word)
<b>Real-Time Clock:</b>	Date and time, 12- or 24-hour format, maintains accurate time without power for up to 30 days typical

<b>Serial Computer Interface:</b>	RS232/RS485 Optional Ethernet Adapter available
<b>Power: (Oak Unit)</b>	Internal power supply 120 VAC, 60Hz, 150 W (230 VAC, 50Hz, 150 W also available)
<b>Power: (Aluminum Unit)</b>	Internal power supply, 200W Universal input, 85-265 VAC, 47-
<b>Maximum Power Cord Length:</b>	6' 7" (204.22 cm)
<b>Keyboard:</b>	Handheld remote operated, infrared, 55 key layout
<b>Case Material:</b>	Solid oak or aluminum
<b>Standard Package Includes:</b>	– Infoschedular electronic sign— – Messaging software – 25-ft. RS232 Cable – 9-pin RJ11 Adapter – IR Keyboard – Installation instructions
<b>Special Features:</b>	Dipswitch selectable serial addressing (Aluminum unit) Optional floor stand
<b>Limited Warranty:</b>	One-year parts and labor, factory servicing
<b>Agency Approvals:</b>	ETL (Conforms to ANSI/UL Std. 1950) IEC 950, EN 60950, certified to CSA STD. C22.2 #950 Complies with part 15 of the FCC rules
<b>Operating Temperature:</b>	32° to 95°F, 0° to 35°C
<b>Humidity Range:</b>	0% to 95% non-condensing
<b>PC Software:</b>	Infoschedular messaging software included, runs on any Pentium PC. Optional scheduling software available

800 473 5623 [www.ledsignage.com](http://www.ledsignage.com)