

Introducing the Worlds 1st One line Full Color Ledsign MMBB-RGB



Case Dimensions:	25 7/8" L x 3 3/16"H x 9/10"D (65.7cm x 9.7cm x 2.3cm)
Display Dimensions:	24.0"L x 2.1"H (61cm x 5.3cm)
Display Weight:	1.5 lbs (.7kg) in-line AC adapter weighs 2.5 lbs (1.1kg)
Display Array:	80 columns x 7 rows
Memory:	16,000 characters
Pixel Size (Diameter):	0.2" (0.51 cm)
Pixel (LED) Color:	Patentd 3-in-one RGB pixel
Center-to-Center Pixel Spacing (Pitch):	0.3" (0.76 cm)
Character (font) Size:	2.1" tall 7 high font (65.3cm tall 7 high font)
Character (font) Array:	5 x 7 or 5 x 5 matrix
Character Sets (fonts):	12 sets: block (sans serif), decorative (serif), upper/lower case, slim/wide, 5 and 7 row high
Memory Retention:	One month typical without power
Message Capacity:	65 different messages can be stored and displayed (or date scheduled)
Message Display Modes:	26 consisting of: Automode™, hold, interlock, roll (6 directions), rotate, compressed rotate, wipe (6 directions), starburst, flash, snow, scroll, sparkle, and cycle colors

Keyboard	Handheld infrared remote, 54 key universal layout
Built-in Animations:	Welcome, sale, news flash, happy 4th, open, closed, thank you, American flag, no smoking, don't drink & drive, fish swimming, fireworks, Christmas and smile
Clock:	12 or 24 hour format
Computer Interface:	USB or RS232 9-pin serial port
Power:	7.5 VDC at 2.9A, 50/60 HZ
Power Cord Length:	10 ft in-line adapter
Case Material:	Injection molded plastic, black
Limited Warranty:	One-year parts and labor, factory servicing
Agency Approvals:	North America: FCC Part 15 Class B, C-ETL-US listed to UL 60950-1 and CSA, 22.2 No. 60950-1, Europe: CISPR 22 Class B, EN 60950-1
Operating Temperature:	32° to 113°F, (0° to 45°C)
Humidity Range:	0% to 95% non-condensing
Mounting	Surface (counter), wall and ceiling brackets, also through-panel mounting

Mandex 800 473 5623
www.zippersonthefly.com



Bend IT



Designed for Exhibit Booths
 Optional convex or concave models
 Bend it. It -30" Radius –better curvature
 Can be achieved by options on the casing.

64 amazing stunning colors

Program direct from your PC with easy use software supplied.

USB/RS232 9 -pin serial port cables included
 Add it to your network with an Ethernet Adapter.
 64 vibrant LED colors for text and animated graphic

Less than one inch thick Ultra-thin, easy-mount casing –
Wow! Can show 27 2" tall letters at 1 time across the screen
 Visible indoor from 75 to 100 feet

Bright enough for shaded windows, no sunlight.

Simple 3 key remote operation

Automode programming!

"Even you can do a great message Instantly"