

MMD WINDOW DISPLAY

- IR keyboard programs the display through your window, 30 ft. distance.
- RS232 or RS485 serial port connects one or multiple displays to your PC.
- Super-bright red, large character size: 4.0"
- 26 exciting operation modes
- Store, schedule and display over 80 messages
- 5 operating speeds for each message
- 6 character fonts for message impact
- Create your own graphics & logos.
- One-year USA factory warranty.
- Software (optional)



Window Display Specifications

Case Dimensions:	49.0"L x 4.25"D x 6.25"H (124.5 cmL x 11.0 cmD x 16.0 cmH)	Message Operating Modes::	Interlock, Roll (6 directions), Rotate, Sparkle-on, Twinkle, Spray-on, Slide across, Switch, Wipe (6 directions), Starburst, Flash, Snow, Scroll, Condensed rotate - Continuous message entry with automatic centering in any mode -User programmable logos and graphics - Five hold speeds
	45.6"L x 4.0"H (115.8 cmL x 10.16cmH)	Built-in Animations:	Cherry-bomb exploding, don't drink and drive, fireworks, slot machine, no smoking, running animal, moving auto, WELCOME (in script) and THANK YOU (in script)
Display Weight:	12.25 lbs. (5.6 kg.)	Clock:	Date and time, 12 or 24 hour format, maintains accurate time without power for up to 14 days typical
Display Array:	80 columns x 7 rows	Serial Computer Interface:	RS232, RS485
Characters displayed:	One line - Typical 14 / Maximum 27	Power:	120 VAC, or 230 VAC optional,

Display memory:	28,000 characters	Maximum Power Cord Length:	10 ft. (3m)
Pixel Size (Diameter):	0.35" (0.89 cm)	Keyboard:	Handheld remote operated, infrared, 54 key layout
Pixel (LED) Color:	Super-bright red	Case Material:	UV stabilized high temperature ABS
Center-to-Center Pixel Spacing (Pitch):	0.57" (10.1 cm)	Limited Warranty:	One-year parts and labor, factory servicing
Character Size:	4.0" tall	Agency Approvals:	ETL (Conforms to EN60950/IEC950 standard -Complies with part 15 of the FCC rules
Character Array:	5 x 7 matrix	Operating Temperature:	32° to 120°F, (0° to 50°C)
Character Sets:	Block (sans serif); decorative (serif); upper/lower case; slim/wide	Humidity Range:	0% to 95% non-condensing
Memory Retention:	2 weeks minimum	Mounting:	Hardware for wall/ceiling mounting is included
Memory Capacity:	80 different messages can be stored and displayed		MMD 800 473 5623

