

MMBB Color LEDSign



This amazing MMBB Display technology, Shows 26 characters at one time in the rotate mode!!!

Case Dimensions:	25.8"L x 2.0" x 3.8"H (65.5 cm x 5.1 cm x 9.7 cm)
Display dimensions:	24.0"L x 2.1"H (61.0 cm x 5.3 cm)
Weight:	2.55 lbs. (1.16 kg.) without power supply and keyboard
Display Array:	80 columns x 7 rows
Display memory:	30,000 characters
Pixel size (diameter):	0.2" (0.51 cm)
Pixel (LED) Color:	8 super-bright colors and 3 rainbow effects
Pitch (center-to-center pixel spacing):	0.3" (0.76 cm)
Character size:	2.1" tall (5.3 cm)
Character array:	5" x 7" LED pixel matrix (12.7 cm x 17.8 cm)
Character set:	Block (sans serif), decorative (serif), upper/lowercase, slim/wide
Memory retention:	One month typical
Message capacity:	26 different pages can be stored, scheduled, and displayed according to time and day of the week
Message capacity:	65 different pages can be stored and displayed
Message operating modes:	26, consisting of: Automode™, Hold, Interlock, Roll (six directions), Rotate, Condensed Rotate, Sparkle, Twinkle, Slide, Switch, Wipe (six directions), Starburst, Flash, Snow, Scroll.
Built-in animations:	Welcome, Slot machine, Trumpet, No smoking, Don't drink and drive, Fish, Fireworks, Balloons, Cherry Bomb, Time/Date
Serial computer interface:	RS232 Optional Windows Software Kit Available
Power:	External power supply 7.5 VDC at 3.25A, 50/60 Hz
Maximum power cord length:	10 feet
Keyboard:	Handheld remote operated, infrared, 54 key layout
Case material:	Extruded aluminum
Clock:	12 or 24 hour format
Limited warranty:	One-year parts and labor, factory servicing
Agency approvals:	<ul style="list-style-type: none">• 120 VAC model listed to:<ul style="list-style-type: none">○ ANSI/UL 1950 3rd edition (US)○ Can/CSA-22.2 No. 950-M89 (Canada)
Operating temperature:	32° to 120° F, 0° to 50° C
Humidity range:	0% to 95% non-condensing
Mounting:	Hardware to accommodate wall/ceiling mounting

