



GLARE-SHIELD™

Glare-Shield™ dissipates sunlight, reducing glare to ensure optimal readability. Content is easier to read than standard displays.



AUTOSHINE™

Adaptive signs detect and auto-adjust to ambient light levels for max clarity and readability day or night, in any weather.



STEEL MOUNTING BRACKET

2" wide, 1/8" thick, 10-gauge, removable (A-Series) HRS angle steel angle mounting brackets and two 1/2" thick steel eye bolts.



CLEAN, SIMPLE DESIGN

Slim-line outdoor-rated cabinet with WiFi and Ethernet quick disconnects and external easy-connect industrial electrical box.



GOLD-PLATED CONNECTIONS

All internal sign connector contacts are gold plated for maximum corrosion protection.



RUGGEDIZED POWER SUPPLY

Solid state, industrial, derated power supply is weather-resistant coated for long life.



100% FRONT SERVICABLE

All internal components are accessible from the display's front for easy maintenance.



LED MODULE BOARD

Ultra-bright, long-lasting, energy-efficient boards deliver over 4,000 quintillion colors.



SOLID STATE CONTROLLER

An industrial-grade control unit delivers reliable, high-detail, high-resolution content.



SURGE PROTECTION

Internal outdoor-grade industrial breaker protects from lightning and power surges.



ADVANCED INTERNAL COOLING

Premium thermal management system prevents premature aging.



INDUSTRIAL-GRADE ENCLOSURE

Scratch/crack resistant, lightweight, durable aluminum protects from extreme weather.

